

Product RELOAD 6-CONCENTRATED GLASS AND STAINLESS CLEANER  
 Revision date 21 June 2017  
 Revision 1



## Safety Data Sheet (SDS)

### Section 1: Identification of the substance/preparation and of the company/undertaking

#### 1.1 Product identifier

**Product name** RELOAD 6-CONCENTRATED GLASS AND STAINLESS CLEANER  
**Product no.** REAQUAGLASS  
**Synonyms, Trade names** No information available.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Cleaning agent.  
**Uses advised against** Any other purpose.

#### 1.3 Details of the supplier of the safety data sheet

**Supplier** Kitchenmaster NI Ltd  
 11 Comber Road  
 Belfast  
 BT8 8AN  
 United Kingdom  
 Tel: 028 9081477 02890812881  
 sales@kitchenmaster-ni.com

**Contact person**

#### 1.4 Emergency telephone number

**Emergency telephone** Emergency Telephone Number: 028 9081 4777 08:30 - 17:00 Monday to Thursday 08:30 - 16:30 Friday

### Section 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (EC 1272/2008)**  
 Physical and chemical hazards Flam. Liq 2- H225  
 Human health Eye Irrit.2A - H319  
 Environment Not classified

#### 2.2 Label elements

**Contains**  
**Detergent labeling** <5% anionic surfactants  
 <5% phosphonates

**Label in accordance with (EC) no. 1272/2008**



**Signal word** Danger

**Hazard statements** H225 Highly flammable liquid and vapour.  
 H319 Causes serious eye irritation.

**Precautionary statements** **Prevention**  
 P210 Keep away from heat/ sparks/open flames/hot surfaces. — No smoking.  
 P280 Wear protective gloves/ protective clothing/eye protection/face protection.  
**Response**

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P370 + P378 In case of fire: Use dry chemical, alcohol resistant foam, carbon dioxide, or water spray for extinction.

**Storage**

P403 + P235 Store in a well-ventilated place. Keep cool.

### 2.3 Other hazards

None known.

## Section 3: Composition/identification of ingredients

### 3.1 Substance

Not applicable.

### 3.2 Mixtures

Name	Product identifier	Reg. EU 1272/2008	%
Ethanol	CAS-No.: 64-17-5 EC No.: 200-578-6 REACH Reg No.: 01-2119457610-43	Eye Irrit.2A - H319, Flam. Liq 2- H225	10-30%
sodium xylenesulphonate	CAS-No.: 1300-72-7 EC No.: 215-090-9	Eye Irrit.2A - H319	1-10%
2-butoxyethanol	CAS-No.: 111-76-2 EC No.: 203-905-0 REACH Reg No.: 01-2119475108-36-0000	Acute Tox 4 - H302, Acute Tox 4 - H312, Acute Tox 4 - H332, Skin Irrit.2 - H315, Eye Irrit.2A - H319	1-10%
sodium hydroxide caustic soda	CAS-No.: 1310-73-2 EC No.: 215-185-5	Skin Corr. 1A - H314	0.01-0.9%

The full text for all hazard statements are displayed in section 16.

#### Composition comments

The data shown are in accordance with the latest EC Directives.

## Section 4: First aid measures

### 4.1 Description of first aid measures

#### General information

Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if symptoms persist, always call a doctor. Seek medical attention for all burns and eye injuries, regardless how minor they may seem. First aid personnel must be aware of own risk during rescue.

#### Inhalation

Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

#### Ingestion

If this product is ingested, remove victim immediately from source of exposure. Rinse mouth thoroughly. Do not induce vomiting. Provide fresh air, warmth and rest. Get medical attention. Never give anything by mouth to an unconscious person.

#### Skin contact

Remove victim immediately from source of exposure. Remove contaminated clothing, shoes and jewelry and wash before reuse. Wash the skin immediately with water. Obtain medical attention if irritation persists or if blistering occurs.

#### Eye contact

Do not rub eye. If this product contacts the eyes, gently flush eyes with water for at least fifteen (15) minutes, lifting the upper and lower eyelids occasionally. Remove contact lenses if present and easy to do so. Avoid contaminating unaffected eye. Seek medical attention.

### 4.2 Most important symptoms and effects, both acute and delayed

#### General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

#### Inhalation

Inhalation of mist or vapor may cause respiratory tract irritation.

#### Ingestion

Exposure to liquid product may cause irritation to mouth, throat and esophagus. May be harmful if swallowed.

#### Skin contact

Prolonged contact with skin may cause irritation.

#### Eye contact

Causes serious eye irritation, including redness and tearing.

**4.3 Indication of any immediate medical attention and special treatment needed**

<b>Notes to the physician</b>	Treat symptomatically.
-------------------------------	------------------------

**Section 5: Fire-fighting measures****5.1 Extinguishing media**

<b>Extinguishing media</b>	Use fire-extinguishing media appropriate for surrounding materials. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
----------------------------	--

<b>Unsuitable extinguishing media</b>	High volume water jet.
---------------------------------------	------------------------

**5.2 Special hazards arising from the substance or mixture**

<b>Hazardous combustion products</b>	During fire, toxic gases (CO, CO <sub>2</sub> ) are formed.
<b>Unusual fire &amp; explosion hazards</b>	Flammable vapours may spread to sources of ignition or accumulate in confined spaces.
<b>Specific hazards</b>	Fire creates: Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ). In the event of damage to packaging, floors may become slippery, avoid falls.

**5.3 Advice for firefighters**

<b>Special fire fighting procedures</b>	If possible, fight fire from protected position. Avoid breathing fire vapours. Ventilate closed spaces before entering them. Containers close to fire should be removed immediately or cooled with water if safe to do so.
---	--

<b>Protective equipment for firefighters</b>	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
--	---

**Section 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

<b>Personal precautions</b>	Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation. Eliminate all sources of ignition. Avoid inhalation of vapours and contact with skin and eyes. In case of inadequate ventilation, use respiratory protection. Do not touch or walk through spilled material. If necessary evacuate surrounding areas.
<b>For emergency responders</b>	Follow safe handling advice and personal protective equipment recommendations for normal use of product.

**6.2 Environmental precautions**

<b>Environmental precautions</b>	Do not discharge onto the ground or into water courses.
----------------------------------	---

**6.3 Methods and material for containment and cleaning up**

<b>Spill clean up methods</b>	Ventilate and evacuate the area. Eliminate all sources of ignition. DO NOT touch spilled material! Stop leak if possible without risk. When dealing with a spillage, wear necessary protective equipment. Absorb spillage with non-combustible, inert absorbent material. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container. Wash thoroughly after dealing with a spillage. Floors may become slippery, avoid falls.
-------------------------------	--

**6.4 Reference to other sections**

<b>Reference to other sections</b>	See section 1 for emergency contact. For personal protection, see section 8. For waste disposal, see section 13.
------------------------------------	--

**Section 7: Handling and storage****7.1 Precautions for safe handling**

<b>Handling</b>	Read and follow manufacturer's recommendations. Use proper personal protection when handling (refer to Section 8). Do not handle broken packages without protective equipment. Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Do not eat, drink or smoke when using the product. Wash thoroughly after handling. Do not
-----------------	--

use contact lenses. Do not mix with other chemicals.

## 7.2 Conditions for safe storage, including any incompatibilities

<b>Storage precautions</b>	Keep upright, locked up and out of reach of children. Keep the product in its original container. Store in cool dry areas away from direct sunlight or sources of ignition.
<b>Storage class</b>	Flammable liquid storage.

## 7.3 Specific end use(s)

<b>Specific end use(s)</b>	The identified uses for this product are detailed in Section 1.2.
<b>Usage description</b>	Use only according to directions. Replace and tighten cap after use.

## Section 8: Exposure controls/Personal protection

### 8.1 Control parameters

Component	STD	TWA (8 Hrs)		STEL (15mins)		Notes
Ethanol	OEL			1000 ppm		
Ethanol	WEL	1000 ppm	1920 mg/m <sup>3</sup>			
2-butoxyethanol	OEL	20 ppm	98 mg/m <sup>3</sup>	50 ppm	246 mg/m <sup>3</sup>	
2-butoxyethanol	WEL	25 ppm	123 mg/m <sup>3</sup>	50 ppm	246 mg/m <sup>3</sup>	
sodium hydroxide caustic soda	OEL				2 mg/m <sup>3</sup>	
sodium hydroxide caustic soda	WEL				2 mg/m <sup>3</sup>	

<b>Ingredient comments</b>	WEL - Workplace Exposure Limits - EH40/2005 Workplace exposure limits. OEL - Occupational Exposure Limit - Ireland, Occupational Exposure Limits 2016.
----------------------------	---

### 8.2 Exposure Controls

#### Protective equipment



<b>Engineering measures</b>	Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.
<b>Respiratory equipment</b>	If ventilation is inadequate, suitable respiratory protection must be worn. EN 136/140/145/143/149. The specific respirator selected must be based on contamination levels found in the work place. Where risk assessment shows air-purifying respirators are appropriate a full face respirator conforming to EN143 should be used, and suitable respirator cartridges as a backup to engineering controls. Use respiratory equipment with gas filter, type A: organic vapours (EN141). Consult manufacturer for specific advice.
<b>Hand protection</b>	Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374) is recommended. (EU Directive 89/686/EEC). Gloves must be inspected prior to use. Suggested material: Butyl-rubber. Consult manufacturer for advice. Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.
<b>Eye protection</b>	Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU).
<b>Other protection</b>	The selected clothing must satisfy the European norm standard EN 943. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
<b>Hygiene measures</b>	Observe normal hygiene standards. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash hands after use.
<b>Process conditions</b>	Ensure that eye flushing systems and safety showers are located close by in the work place.

---

**Section 9: Physical and chemical properties**


---

**9.1 Information on basic physical and chemical properties**

<b>Appearance</b>	Liquid.
<b>Colour</b>	Green. Clear.
<b>Odour</b>	No information available.
<b>Odour threshold - lower</b>	No information available.
<b>Odour threshold - upper</b>	No information available.
<b>pH-Value, Conc. Solution</b>	>11.
<b>pH-Value, Diluted solution</b>	No information available.
<b>Melting point</b>	No information available.
<b>Initial boiling point and boiling range</b>	No information available.
<b>Flash point</b>	No information available.
<b>Evaporation rate</b>	No information available.
<b>Flammability state</b>	No information available.
<b>Flammability limit - lower(%)</b>	No information available.
<b>Flammability limit - upper(%)</b>	No information available.
<b>Vapour pressure</b>	No information available.
<b>Vapour density (air=1)</b>	No information available.
<b>Relative density</b>	0.976 +/- 0.005.
<b>Bulk density</b>	No information available.
<b>Solubility</b>	Soluble in water.
<b>Decomposition temperature</b>	No information available.
<b>Partition coefficient; n-Octanol/Water</b>	No information available.
<b>Auto ignition temperature (°C)</b>	No information available.
<b>Viscosity</b>	No information available.
<b>Explosive properties</b>	Not classified as explosive.
<b>Oxidising properties</b>	No information available.

**9.2 Other information**

<b>Molecular weight</b>	No information available.
<b>Volatile organic compound</b>	No information available.
<b>Other information</b>	None noted.

---

**Section 10: Stability and reactivity**


---

**10.1 Reactivity**

<b>Reactivity</b>	Reactions may occur with strong acids and strong oxidizing agents. Flammable liquid. Stable under normal conditions.
-------------------	--

**10.2 Chemical stability**

**Stability** Stable under normal temperature conditions and recommended use.

**10.3 Possibility of hazardous reactions**

**Hazardous reactions** See section 10.1 for information on hazardous reactions.  
**Hazardous polymerisation** No information available.  
**Polymerisation description** Not applicable.

**10.4 Conditions to Avoid**

**Conditions to avoid** Heat, sparks, open flames, temperature extremes and direct sunlight.

**10.5 Incompatible materials**

**Materials to avoid** Keep away from acids and oxidants. Do not mix with other chemicals unless listed on directions.

**10.6 Hazardous decomposition products**

**Hazardous decomposition products** Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

**Section 11: Toxicological information****11.1 Information on toxicological effects**

**Toxicological information** No toxicological information for the overall finished product.

**Acute toxicity (Oral LD50)** 2-BUTOXYETHANOL (CAS 111-76-2): 1746 mg/kg, Rat. REACH dossier information.  
 SODIUM HYDROXIDE (CAS 1310-73-2): 325 mg/kg, bw Rabbit. REACH dossier information.  
 SODIUM XYLENE SULPHONATE (CAS 1300-72-7): > 7000 mg/kg, Rat. REACH dossier information.

**Acute toxicity (Dermal LD50)** 2-BUTOXYETHANOL (CAS 111-76-2): 0.63 mL/kg, Rabbit. REACH dossier information.  
 SODIUM HYDROXIDE (CAS 1310-73-2): 1350 mg/kg, Rabbit. IUCLID chemical data sheet.  
 SODIUM XYLENE SULPHONATE (CAS 1300-72-7): > 2000 mg/kg. REACH dossier information.

**Acute toxicity (Inhalation LD50)** 2-BUTOXYETHANOL (CAS 111-76-2): 450 ppm (vapours, Rat, 4 hours.) REACH dossier information.

**Serious eye damage/irritation** Causes serious eye irritation.

**Skin corrosion/irritation** No information available.

**Respiratory sensitisation** No information available.  
**Skin sensitisation** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** No information available.

**Specific target organ toxicity - Single exposure:**  
**STOT - Single exposure** No information available.  
**Specific target organ toxicity - Repeated exposure:**  
**STOT - Repeated exposure** No information available.

**Inhalation** Inhalation of mist or vapor may cause respiratory tract irritation.  
**Ingestion** Exposure to liquid product may cause irritation to mouth, throat and esophagus. May be harmful if swallowed.

**Skin contact** Prolonged contact with skin may cause irritation.  
**Eye contact** Causes serious eye irritation, including redness and tearing.

**Waste management** When handling waste, consideration should be made to the safety precautions applying to handling of the product.

**Routes of entry** No information available.  
**Target organs** Eyes, skin, digestive system, respiratory system.

**Aspiration hazards:** No information available.

**Reproductive toxicity:** No information available.

Name	LD50 oral	LD50 dermal	LD50 inhalation
Sulfonic acids, C14-16-alkane hydroxy and C14-1-alkene, sodium salts	>2000.00mg/kg Rat		
Ethanol	>2000.00mg/kg Rat	>2000.00mg/kg Rabbit	>20.00mg/l (vapours) Rat 4 Hours

## Section 12: Ecological information

### 12.1 Toxicity

<b>Acute toxicity - Fish</b>	2-BUTOXYETHANOL (CAS 111-76-2) LC50: (96 hours) 1474 mg/l, Oncorhynchus mykiss (Rainbow trout.) REACH dossier information. SODIUM HYDROXIDE (CAS 1310-73-2) LC50: (96 hours) 45.4 mg/l, Oncorhynchus mykiss (Rainbow trout.) IUCLID chemical data sheet. SODIUM XYLENE SULPHONATE (CAS 1300-72-7) LC50: (96 hours) > 1000 mg/l, Oncorhynchus mykiss (Rainbow trout.) REACH dossier information.
<b>Acute toxicity - Aquatic invertebrates</b>	2-BUTOXYETHANOL (CAS 111-76-2) EC50: (48 hours) 1550 mg/l, Daphnia magna. REACH dossier information. SODIUM HYDROXIDE (CAS 1310-73-2) EC50: (48 hours) 40.4 ug/L, Ceriodaphnia sp. REACH dossier information. SODIUM XYLENE SULPHONATE (CAS 1300-72-7) EC50: (48 hours) > 1020 mg/l, Daphnia magna. REACH dossier information.
<b>Acute toxicity - Aquatic plants</b>	2-BUTOXYETHANOL (CAS 111-76-2) EC50: (72 hr) 911 mg/l, NOEC: (72hr) 88 mg/l, Pseudokirchneriella subcapitata. REACH dossier information. SODIUM XYLENE SULPHONATE (CAS 1300-72-7) EC50: (96 hours) 758 mg/l, Pseudokirchneriella subcapitata. REACH dossier information.
<b>Acute toxicity - Microorganisms</b>	No information available.
<b>Chronic toxicity - Fish</b>	No information available.
<b>Chronic toxicity - Aquatic invertebrates</b>	No information available.
<b>Chronic toxicity - Aquatic plants</b>	No information available.
<b>Chronic toxicity - Microorganisms</b>	No information available.
<b>Ecotoxicity</b>	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
<b>Eco toxicological information</b>	No ecological toxicity available on the overall finished product.

### 12.2 Persistence and degradability

<b>Degradability</b>	The degradability of the product has not been stated.
<b>Biological oxygen demand</b>	No information available.
<b>Chemical oxygen demand</b>	No information available.

### 12.3 Bioaccumulative potential

<b>Bioaccumulative potential</b>	No data available on bioaccumulation.
<b>Bioaccumulation factor</b>	No information available.
<b>Partition coefficient; n-Octanol/Water</b>	No information available.

### 12.4 Mobility in soil

<b>Mobility</b>	Soluble in water.
-----------------	-------------------

### 12.5 Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** No information available.

### 12.6 Other adverse effects

**Other adverse effects** None known.

Name	Acute toxicity (Fish)	Acute toxicity (Aquatic invertebrates)	Acute toxicity (Aquatic plants)

Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts	LC50 96 Hours 12.20mg/l Freshwater Fish	LC50 48 Hours 4.53mg/l Daphnia magna	
Ethanol	LC50 96 Hours 15300.00mg/l Pimephales promelas (Fat-head Minnow)	EC50 48 Hours >10000.00mg/l Daphnia magna	

---

**Section 13: Disposal considerations**


---

**Waste management** When handling waste, consideration should be made to the safety precautions applying to handling of the product.

**13.1 Waste treatment methods**

**Disposal methods** Dispose of waste and residues in accordance with local authority requirements.

---

**Section 14: Transport information**


---

**14.1 UN number**

UN no. (ADR) UN1993  
 UN no. (IMDG) UN1993  
 UN no. (IATA) UN1993

**14.2 UN proper shipping name**

ADR proper shipping name FLAMMABLE LIQUID, N.O.S. (Ethanol)  
 IMDG proper shipping name FLAMMABLE LIQUID, N.O.S. (Ethanol)  
 IATA proper shipping name FLAMMABLE LIQUID N.O.S. (Ethanol)

**14.3 Transport hazard class(es)**

ADR class 3  
 IMDG class 3  
 IATA class 3

**Transport labels****14.4 Packing group**

ADR/RID/ADN packing group II  
 IMDG packing group II  
 IATA packing group II

**14.5 Environmental hazards**

ADR No  
 IMDG No  
 IATA No

**14.6 Special precautions for user**

EMS F-E, S-E  
 Emergency action code A3 A148  
 Hazard no. (ADR) 33  
 Tunnel restriction code (D/E)

**14.7 Transport in bulk according to annex II of MARPOL73/78 and the IBC code**

Not applicable.

---

**Section 15: Regulatory information**


---

**15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture**



<b>EU legislation</b>	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The UN Globally Harmonized System (GHS) Safety Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 453/2010 of 20th May 2010 amending regulation (EC) No 1907/2006.
<b>Approved code of practice</b>	Workplace Exposure Limits Guidance Note EH40/2005.  2016 Code of Practice for the Chemical Agents Regulations in accordance with section 60 of the Safety, Health and Welfare at Work Act 2005 (No. 10 of 2005).
<b>Chemical safety assessment</b>	No chemical safety assessment has been carried out.

---

**Section 16: Other information**

---

<b>General information</b>	This Safety Data Sheet is in accordance with Reach Regulation (EC) No 453/2010.
<b>Revision comments</b>	This is a first issue.
<b>Revision date</b>	21 June 2017
<b>Revision</b>	1
<b>Safety data sheet status</b>	Approved.

**Hazard statements in full**

<b>H225</b>	Highly flammable liquid and vapour.
<b>H319</b>	Causes serious eye irritation.
<b>H302</b>	Harmful if swallowed.
<b>H312</b>	Harmful in contact with skin.
<b>H315</b>	Causes skin irritation.
<b>H332</b>	Harmful if inhaled.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H317</b>	May cause an allergic skin reaction.
<b>H400</b>	Very toxic to aquatic life.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.
<b>H361</b>	Suspected of damaging fertility or the unborn child .
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>H318</b>	Causes serious eye damage.
<b>H301</b>	Toxic if swallowed.
<b>H311</b>	Toxic in contact with skin.
<b>H331</b>	Toxic if inhaled.
<b>H304</b>	May be fatal if swallowed and enters airways.

**Disclaimer**

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.