ProductLime DisinfectantRevision date21 June 2017Revision1



# Safety Data Sheet (SDS)

## Section 1: Identification of the substance/preparation and of the company/undertaking

#### **1.1 Product identifier**

Product name	Lime Disinfectant
Product no.	DISLIME
Synonyms, Trade names	No information available.

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Disinfectant.
Uses advised against	No uses advised against are identified.

#### **1.3 Details of the supplier of the safety data sheet**

Supplier	Kitchenmaster NI Ltd
	11 Comber Road
	Belfast
	BT8 8AN
	United Kingdom
	Tel: 028 9081477 02890812881
Contact person	sales@kitchenmaster-ni.com
1.4 Emergency telephone number	
Emergency telephone	Emergency Telephone Number: 028 9081 4777 08:30 – 17:00 Monday to Thursday 08:30 – 16:30 Friday

#### Section 2: Hazards identification

## 2.1 Classification of the substance or mixture

Classification (EC 1272/2008)	
Physical and chemical hazards	Not classified
Human health	Eye Irrit.2A - H319
Environment	Not classified

#### 2.2 Label elements

#### Contains

Alcohols, C12-15, ethoxylated Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides

Label in accordance with (EC) no. 1272/2008



Signal word

Danger

**Hazard statements** 

**Precautionary statements** 

H319 Causes serious eye irritation.

## Prevention

P264 Wash thoroughly after handling. P280 Wear protective gloves/ protective clothing/eye protection/face protection. **Response** P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/attention.

## 2.3 Other hazards

None known.

## Section 3: Composition/identification of ingredients

## 3.1 Substance

Not applicable.

## 3.2 Mixtures

Name	Product identifier	Reg. EU 1272/2008	%
Alcohols, C12-15, ethoxylated	CAS-No.: 68131-39-5 EC No.: 500-195-7	Eye Dam. 1 - H318, Aquatic Acute 1 - H400, Aquatic Chronic 3 - H412	1-10%
Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides	EC No.: 270-325-2	Dam. 1 - H318, Aquatic Acute 1 - H400	0-1%
bornan-7-one	CAS-No.: 76-22-2 EC No.: 200-945-0	Flam. Sol 2- H228, Acute Tox 4 - H302, Acute Tox 4 - H332, STOT SE 2 - H371	0-1%

The full text for all hazard statements are displayed in section 16.

**Composition comments** 

The data shown are in accordance with the latest EC Directives.

# Section 4: First aid measures

## **4.1 Description of first aid measures**

General information	Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if symptoms persist, always call a doctor. Seek medical attention for all burns and eye injuries, regardless how minor they may seem. First aid personnel must be aware of own risk during rescue.
Inhalation	Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.
Ingestion	If this product is ingested, remove victim immediately from source of exposure. Rinse mouth thoroughly. Do not induce vomiting. Provide fresh air, warmth and rest. Get medical attention. Never give anything by mouth to an unconscious person.
Skin contact	Remove victim immediately from source of exposure. Remove contaminated clothing, shoes and jewelry and wash before reuse. Wash the skin immediately with water. Obtain medical attention if irritation persists or if blistering occurs.
Eye contact	Do not rub eye. If this product contacts the eyes, gently flush eyes with water for at least fifteen (15) minutes, lifting the upper and lower eyelids occasionally. Remove contact lenses if present and easy to do so. Avoid contaminating unaffected eye. Seek medical attention.

# 4.2 Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the
	length of exposure.
Inhalation	No specific symptoms noted.
Ingestion	May cause discomfort if swallowed.
Skin contact	Skin contact may cause redness and irritation.
Eye contact	Causes serious eye irritation.

# 4.3 Indication of any immediate medical attention and special treatment needed

Notes to the physician	Treat symptomatically.
------------------------	------------------------

# **Section 5: Fire-fighting measures**

## 5.1 Extinguishing media

Extinguishing media Unsuitable extinguishing media Use fire-extinguishing media appropriate for surrounding materials. None noted.

# 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products Unusual fire & explosion hazards Specific hazards	During fire, toxic gases (CO, CO2) are formed. No unusual fire or explosion hazards noted. Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).
5.3 Advice for firefighters	
Special fire fighting procedures	If possible, fight fire from protected position. Avoid breathing fire vapours. Ventilate closed spaces before entering them. Containers close to fire should be removed immediately or cooled with water if safe to do so.
Protective equipment for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

#### Section 6: Accidental release measures

# $\underline{6.1}$ Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation. Eliminate all sources of ignition. Avoid inhalation of vapours and contact with skin and eyes. In case of inadequate ventilation, use respiratory protection. Do not touch or walk through spilled material. If necessary evacuate surrounding areas.
For emergency responders	Follow safe handling advice and personal protective equipment recommendations for normal use of product.
6.2 Environmental precautions	
<b>Environmental precautions</b>	Do not discharge onto the ground or into water courses.
6.3 Methods and material for containm	ent and cleaning up
Spill clean up methods	Stop leak if possible without risk. Eliminate all sources of ignition. Ventilate and evacuate the area. DO NOT touch spilled material! When dealing with a spillage, wear necessary protective equipment. Absorb spillage with non-combustible, inert absorbent material. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container. Wash thoroughly after dealing with a spillage.
6.4 Reference to other sections	
Reference to other sections	See section 1 for emergency contact. For personal protection, see section 8. For waste disposal, see section 13.
Section 7: Handling and storage	
7.1 Precautions for safe handling	
Handling	Read and follow manufacturer's recommendations. Use proper personal protection when handling (refer to Section 8). Do not handle broken packages without protective equipment. Do not use contact lenses. Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Do not eat, drink or smoke when using the product. Wash thoroughly after handling.
7.2 Conditions for safe storage, includi	ng any incompatibilities

# Storage precautionsKeep upright, locked up and out of reach of children. Keep the product in its original<br/>container. Store in cool dry areas away from direct sunlight or sources of ignition. Keep<br/>away from incompatible materials (see section 10).<br/>Chemical storage.Storage classThe identified uses for this product are detailed in Section 1.2.<br/>Use only according to directions. Replace and tighten cap after use.

# Section 8: Exposure controls/Personal protection


# **8.1 Control parameters**

Component	STD	TWA (	8 Hrs)	STEL (1	5mins)	Notes
bornan-2-one	OEL	2 ppm	12 mg/m <sup>3</sup>	3 ppm	18 mg/m <sup>3</sup>	
bornan-2-one	WEL	2 ppm	13 mg/m <sup>3</sup>	3 ppm	19 mg/m <sup>3</sup>	

Ingredient comments

WEL - Workplace Exposure Limits - EH40/2005 Workplace exposure limits. OEL - Occulational Exposure Limit - Ireland, Occupational Exposure Limits 2016.

# **8.2 Exposure Controls**



Respiratory equipmentdefined occupational exposure limit is not exceeded.If ventilation is inadequate, suitable respiratory protection must be worn. EN 136/140/145/143/149. The specific respirator selected must be based on contamination levels found in the work place. Where risk assessment shows air-purifying respirators are appropriate a full face respirator conforming to EN143 should be used, and suitable respirator cartridges as a backup to engineering controls. Recommended: Respirator with combination filter for vapour/particulate (EN 141). Consult manufacturer for specific advice.Hand protectionWhere hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374) is recommended. (EU Directive 89/686/EEC). Gloves must be inspected prior to use. Suggested material: Butyl-rubber. Breakthrough time: >480 minutes. Minimum layer thickness: 0.33 mm. Consult manufacturer for advice.Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.Eye protectionWear safety goggles or face shield to prevent any possibility of eye contact. Use equipment
136/140/145/143/149. The specific respirator selected must be based on contamination levels found in the work place. Where risk assessment shows air-purifying respirators are appropriate a full face respirator conforming to EN143 should be used, and suitable respirator cartridges as a backup to engineering controls. Recommended: Respirator with combination filter for vapour/particulate (EN 141). Consult manufacturer for specific advice.Hand protectionWhere hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374) is recommended. (EU Directive 89/686/EEC). Gloves must be inspected prior to use. Suggested material: Butyl-rubber. Breakthrough time: >480 minutes. Minimum layer thickness: 0.33 mm. Consult manufacturer for advice. Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.
Hand protectionfound in the work place. Where risk assessment shows air-purifying respirators are appropriate a full face respirator conforming to EN143 should be used, and suitable respirator cartridges as a backup to engineering controls. Recommended: Respirator with combination filter for vapour/particulate (EN 141). Consult manufacturer for specific advice.Hand protectionWhere hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374) is recommended. (EU Directive 89/686/EEC). Gloves must be inspected prior to use. Suggested material: Butyl-rubber. Breakthrough time: >480 minutes. Minimum layer thickness: 0.33 mm. Consult manufacturer for advice. Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.
appropriate a full face respirator conforming to EN143 should be used, and suitable respirator cartridges as a backup to engineering controls. Recommended: Respirator with combination filter for vapour/particulate (EN 141). Consult manufacturer for specific advice.Hand protectionWhere hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374) is recommended. (EU Directive 89/686/EEC). Gloves must be inspected prior to use. Suggested material: Butyl-rubber. Breakthrough time: >480 minutes. Minimum layer thickness: 0.33 mm. Consult manufacturer for advice. Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.
Hand protectionrespirator cartridges as a backup to engineering controls. Recommended: Respirator with combination filter for vapour/particulate (EN 141). Consult manufacturer for specific advice.Hand protectionWhere hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374) is recommended. (EU Directive 89/686/EEC). Gloves must be inspected prior to use. Suggested material: Butyl-rubber. Breakthrough time: >480 minutes. Minimum layer thickness: 0.33 mm. Consult manufacturer for advice. Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.
Hand protectioncombination filter for vapour/particulate (EN 141). Consult manufacturer for specific advice. Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374) is recommended. (EU Directive 89/686/EEC). Gloves must be inspected prior to use. Suggested material: Butyl-rubber. Breakthrough time: >480 minutes. Minimum layer thickness: 0.33 mm. Consult manufacturer for advice. Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.
Hand protectionWhere hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374) is recommended. (EU Directive 89/686/EEC). Gloves must be inspected prior to use. Suggested material: Butyl-rubber. Breakthrough time: >480 minutes. Minimum layer thickness: 0.33 mm. Consult manufacturer for advice. Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.
standards (e.g. Europe: EN374) is recommended. (EU Directive 89/686/EEC). Gloves must be inspected prior to use. Suggested material: Butyl-rubber. Breakthrough time: >480 minutes. Minimum layer thickness: 0.33 mm. Consult manufacturer for advice. Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.
inspected prior to use. Suggested material: Butyl-rubber. Breakthrough time: >480 minutes. Minimum layer thickness: 0.33 mm. Consult manufacturer for advice. Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.
Minimum layer thickness: 0.33 mm. Consult manufacturer for advice. Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.
Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.
diffusion and degradation, and concentration specific to the workplace. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.
removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.
product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.
good laboratory practices.
5 5 1
<b>Eye protection</b> Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment
for eye protection tested and approved under appropriate government standards such as EN
166(EU).
<b>Other protection</b> The selected clothing must satisfy the European norm standard EN 943. Personal protective
equipment for the body should be selected based on the task being performed and the risks
involved and should be approved by a specialist before handing this product.
<b>Hygiene measures</b> Observe normal hygiene standards. Wash promptly if skin becomes contaminated. When
using do not eat, drink or smoke. Wash hands after use.
<b>Process conditions</b> Ensure that eye flushing systems and safety showers are located close by in the work place.

# **Section 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Appearance Colour Odour	Liquid. Light Green. No information available.
Odour threshold - lower	No information available.
Odour threshold - upper	No information available.
pH-Value, Conc. Solution	6.00
pH-Value, Diluted solution	5.50 - 6.50
Melting point	No information available.
Initial boiling point and boiling	No information available.

range
-------

Flash point	No information available.
<b>Evaporation rate</b>	No information available.
Flammability state	No information available.
Flammability limit - lower(%)	No information available.
Flammability limit - upper(%)	No information available.
Vapour pressure	No information available.
Vapour density (air=1)	No information available.
Relative density	1.0g/cm <sup>3</sup> @ 20.00 °C
Bulk density	No information available.
Solubility	Soluble in water.
Decomposition temperature	No information available.
Partition coefficient; n- Octanol/Water	No information available.
Auto ignition temperature (°C)	No information available.
Viscosity	No information available.
Explosive properties	Not classified as explosive.
Oxidising properties	No information available.
9.2 Other information	
Molecular weight	No information available.
Volatile organic compound	No information available.
Other information	None noted.

Section	10:	Stability	and	reactivity
---------	-----	-----------	-----	------------

10.1 Reactivity	
Reactivity	Reactions may occur with strong acids and strong oxidizing agents.
<u>10.2 Chemical stability</u> Stability	Stable under normal temperature conditions and recommended use.
<b>10.3 Possibility of hazardous reactions</b>	
Hazardous reactions Hazardous polymerisation Polymerisation description	For information on hazardous reactions see section 10.1. Will not polymerise. Not applicable.
<b>10.4 Conditions to Avoid</b>	
Conditions to avoid	Heat, sparks, open flames, temperature extremes and direct sunlight. Avoid storing in large quantities or for long periods of time.
10.5 Incompatible materials	
Materials to avoid	Do not mix with other chemicals unless listed on directions. Avoid strong oxidising agents, bases, strong acids.

# **10.6 Hazardous decomposition products**

Hazardous decomposition products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

# Section 11: Toxicological information

# **<u>11.1 Information on toxicological effects</u>**

Toxicological information	No toxicological information for the overall finished product.
Acute toxicity (Oral LD50) Acute toxicity (Dermal LD50) Acute toxicity (Inhalation LD50)	Alcohols, C12 -15, ethoxylated: > 5000 mg/kg Rat. Alcohols, C12 -15, ethoxylated: > 2000 mg/kg Rat. Alcohols, C12 -15, ethoxylated: > 1.6 mg/l (dust/mist) Rat 4 hours.
Serious eye damage/irritation	Causes serious eye damage.
Skin corrosion/irritation	No information available.
Respiratory sensitisation Skin sensitisation	No information available. No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Specific target organ toxicity - Sing STOT - Single exposure Specific target organ toxicity - Repo STOT - Repeated exposure	No information available.
Inhalation Ingestion Skin contact Eye contact Waste management	No specific symptoms noted. May cause discomfort if swallowed. Skin contact may cause redness and irritation. Causes serious eye irritation. When handling waste, consideration should be made to the safety precautions applying to handling of the product.
Routes of entry Target organs	No information available. Eyes, skin, digestive system, respiratory system.
Aspiration hazards: Reproductive toxicity:	No information available. No information available.

# Section 12: Ecological information

# 12.1 Toxicity

Acute toxicity - Fish Acute toxicity - Aquatic invertebrate Acute toxicity - Aquatic plants Acute toxicity - Microorganisms Chronic toxicity - Fish Chronic toxicity - Aquatic invertebrates	Alcohols, C12 -15, ethoxylated: LC50 96 hours 0.59 mg/l Pleuronectes platessa. s Alcohols, C12 -15, ethoxylated: EC50 48 hours 0.14 mg/l Daphnia magna. Alcohols, C12 -15, ethoxylated: EC50 72 hours 0.75 mg/l Selenastrum capricornutum. No information available. No information available. No information available.
Chronic toxicity - Aquatic plants Chronic toxicity - Microorganisms Ecotoxicity	No information available. No information available. The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Eco toxilogical information	No ecological toxicity available on the overall finished product.
<b>12.2 Persistence and degradability</b>	
Degradability Biological oxygen demand Chemical oxygen demand	The degradability of the product has not been stated. No information available. No information available.

<b>12.3 Bioaccumulative potential</b>	
Bioaccumulative potential Bioacculmation factor Partition coefficient; n- Octanol/Water	No data available on bioaccumulation. No information available. No information available.
<u>12.4 Mobility in soil</u>	
Mobility	Soluble in water.
12.5 Results of PBT and vPvB assessme	ent
Results of PBT and vPvB assessmen	t The product does not contain any PBT or vPvB Substances.
12.6 Other adverse effects	
Other adverse effects	None known.
Section 13: Disposal considerations	
Waste management	When handling waste, consideration should be made to the safety precautions applying to
5	handling of the product.
13.1 Waste treatment methods	
Disposal methods	Dispose of waste and residues in accordance with local authority requirements.
Section 14: Transport information	
<u>14.1 UN number</u>	
UN no. (ADR) UN no. (IMDG)	Not applicable. Not applicable.
UN no. (IATA)	Not applicable.
<b>14.2 UN proper shipping name</b>	
ADR proper shipping name IMDG proper shipping name	Not applicable. Not applicable.
IATA proper shipping name	Not applicable.
14.3 Transport hazard class(es)	
ADR class	Not applicable.
IMDG class IATA class	Not applicable. Not applicable.
Transport labels	Not applicable
14.4 Packing group	
ADR/RID/ADN packing group	Not applicable.
IMDG packing group IATA packing group	Not applicable. Not applicable.
14.5 Environmental hazards	
ADR	No
IMDG IATA	No No
14.6 Special precautions for user	
EMS	Not applicable.
Emergency action code Hazard no. (ADR)	Not applicable. Not applicable.
Tunnel restriction code	Not applicable.

# 14.7 Transport in bulk according to annex II of MARPOL73/78 and the IBC code

Not applicable.

## Section 15: Regulatory information

# 15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The UN Globally Harmonized System (GHS) Safety Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 453/2010 of 20th May 2010 amending regulation (EC) No 1907/2006.
Approved code of practice	Workplace Exposure Limits Guidance Note EH40/2005.
	2016 Code of Practice for the Chemical Agents Regulations in accordance with section 60 of the Safety, Health and Welfare at Work Act 2005 (No. 10 of 2005).
Chemical safety assessment	No chemical safety assessment has been carried out.

#### **Section 16: Other information**

General information	This Safety Data Sheet is in accordance with Reach Regulation (EC) No 453/2010.
<b>Revision comments</b>	This is a first issue.
Revision date	21 June 2017
Revision	1
Safety data sheet status	Approved.

#### Hazard statements in full

H302	Harmful if swallowed.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H226	Flammable liquid and vapour.
H410	Very toxic to aquatic life with long lasting effects.
H228	Flammable solid.
H332	Harmful if inhaled.
H371	May cause damage to organs .
H304	May be fatal if swallowed and enters airways.

#### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.